


**■Features**

- Infrared Light Emitting Diode
- 880nm, 65mW
- Viewing angle: 20deg
- Package: 5mm clear epoxy
- UV Resistant Epoxy

**■Applications**

- IrDA
- Encoder
- Data Communication
- IR camera

**■Outline Dimension**




**■Absolute Maximum Rating**

(Ta=25°C)

| Item                       | Symbol           | Value      | Unit |
|----------------------------|------------------|------------|------|
| DC Forward Current         | I <sub>F</sub>   | 100        | mA   |
| Pulse Forward Current*     | I <sub>FP</sub>  | 200        | mA   |
| Reverse Voltage            | V <sub>R</sub>   | 5          | V    |
| Power Dissipation          | P <sub>D</sub>   | 190        | mW   |
| Operating Temperature      | T <sub>opr</sub> | -30 ~ +85  | °C   |
| Storage Temperature        | T <sub>stg</sub> | -40~ +100  | °C   |
| Lead Soldering Temperature | T <sub>sol</sub> | 260°C/5sec | -    |

\*Pulse width Max.10ms Duty ratio max 1/10

**■Directivity**



**■Electrical -Optical Characteristics**

(Ta=25°C)

| Item               | Symbol            | Condition             | Min. | Typ. | Max. | Unit  |
|--------------------|-------------------|-----------------------|------|------|------|-------|
| DC Forward Voltage | V <sub>F</sub>    | I <sub>F</sub> =100mA | -    | 1.6  | 2.0  | V     |
| DC Reverse Current | I <sub>R</sub>    | V <sub>R</sub> =5V    | -    | -    | 10   | μA    |
| Peak Wavelength    | λ <sub>p</sub>    | I <sub>F</sub> =100mA | 866  | 880  | 892  | nm    |
| Radiant Intensity  | I <sub>e</sub>    | I <sub>F</sub> =100mA | 150  | 220  | 330  | mW/Sr |
| Radiant Power      | P <sub>O</sub>    | I <sub>F</sub> =100mA | 50   | 65   | 80   | mW    |
| 50% Power Angle    | 2θ <sub>1/2</sub> | I <sub>F</sub> =100mA | -    | 20   | -    | deg   |

\*1 Tolerance of measurements of Peak wavelength is ±1nm

\*2 Tolerance of measurements of Radiant Power is ±15%

\*3 Tolerance of measurements of forward voltage is ±0.1V